



VP220 PRO

Synthesized two tone voice pager
with caller ID LCD display

- Speaker /earphone jack
- Twelve call per channel / 8 individual and 4 group call
- 480 seconds memory (16 stored voice, each for 30 sec) optional function feature
- Loud clear alert level
- Large volume control knobs with on/off Switch
- Function switch: different function switch will be configured to 4 position.
- Two channels
- Silent & Priority Scan
- Programmable Narrowband / Wideband Channel Spacing
- IP54 approved for water & dust repellance
- Loud clear alert level: 93dBa at 12 inches distance
- Priority alert programmable
- Monitor channel function
- Operates on 3 AAA Ni-HM rechargeable battery or 3 AAA alkaline battery
- Desktop charger standard
- Low Battery indicator
- Strong belt clip
- Message reminder tone with LED flashing light

SPECIFICATIONS

Tone Coding:	Two -Tone Sequential			
Frequency:	VHF	UHF		
	135~174MHz	404~512MHz	(call office for exact frequency splits)	
Wide Band/Narrow Band	WB	NB	WB	NB
Channel Spacing:	25KHz/12.5KHz			
Alerting:	4uV/m	4uV/m	3.5uV/m	3.5uV/m
Adjacent channel selectivity:	60dB +/-25KHz	50dB +/-12.5KHz	60dB +/-25KHz	50dB +/-12.5KHz
Spurious Rejection:	60dB below carrier		50dB below carrier	
1'st Image Rejection:	60dB below carrier		50dB below carrier	
2'nd Image Rejection:	60dB below carrier		60dB below carrier	
Frequency Stability:	+/-10ppm		+/- 3ppm	
Audio Output:	90dBa at 30cm (12)			
Alert Tone:	93dBa at 30cm (12)			
Power Consumption:	9mA (without power save)			
Power Supply:	NiMH 3 x 1.2V AAA-size 950mAh rechargeable battery (1.2V)			
NiMH	About 14 days (7 days without battery saver)			
	Based on an 8 hour day / 5 messages per day @ 30 seconds each			
Weight (with battery):	Approximately 186 g			
Dimension:	104(L)x62(W)x30(H)mm			

