

# DIGITAL PAGING COMPANY

## Apollo

### VP100 VOICE PAGER

#### FEATURES:

- ONE CHANNEL / SYNTHESIZED
- NARROW AND WIDEBAND CAPABLE
- SIX CALLS PER CHANNEL
- 120 SECOND STORED VOICE MEMORY
- TONE & VIBRATE ALERTS
- PRIORITY ALERT PROGRAMMABLE
- MONITOR CHANNEL FUNCTION
- MONITOR WITH CARRIER SQUELCH
- LOW BATTERY TONE ALERT
- AUDIO LOCK ON FEATURE
- MULTIPLE ALERT TONES
- MESSAGE REMINDER TONE ALERT & LED ALERT
- EXTERNAL EARPHONE JACK
- SLIDE ON/OFF SWITCH WITH VIBRATE, & ALERT SELECTIONS
- STANDARD DESKTOP CHARGER
- OPERATES ON ONE AA NI-HM OR NI-CAD RECHARGEABLE BATTERY OR ONE AA ALKALINE BATTERY
- 2 STATUS LED ALERT LIGHTS
- MANUAL RESET
- AUTO RESET REVERT WITH SQUELCH
- OPTIONAL PUSH TO LISTEN FEATURE
- PROGRAMMABLE DISABLE POWER OFF & VIBRATE FEATURES



#### GENERAL SPECIFICATIONS:

FREQUENCY RANGE	143 – 174 MHz	406 – 430, 450 – 512MHz
MAX. FREQ. SEPERATION	8MHz	8 MHz
ALERT SENSITIVITY	5uv/m	5uv/m
SELECTIVITY	60dB	60dB
SPURIOUS IMAGE REJECTION	55dB	55dB
AUDIO OUTPUT (12" DISTANCE)	90/88dB	90/88dB
FREQUENCY STABILITY	10ppm	10ppm
PROGRAMMABLE ADDRESSES	6	6
VOICE STORAGE TIME	2 Minutes	2 Minutes
POWER SUPPLY	1.2V NI-HM AA BATTERY	
BATTERY LIFE	APPROXIMATELY 10 DAYS	

#### For More Information Contact:

Digital Paging Company, North Hollywood, CA  
Tel: (800) 540-5700x33 Fax: (818) 508-5800  
Web: [www.apollowireless.com](http://www.apollowireless.com)

**dpc**

Digital Paging Company

## VP100 TONE VOICE PAGER

### FEATURES:

- ONE CHANNEL / SYNTHESIZED
- NARROW AND WIDEBAND CAPABLE
- SIX CALLS PER CHANNEL
- 120 SECOND STORED VOICE MEMORY
- TONE & VIBRATE ALERTS
- PRIORITY ALERT PROGRAMMABLE
- MONITOR CHANNEL FUNCTION
- MONITOR WITH CARRIER SQUELCH
- LOW BATTERY TONE ALERT
- AUDIO LOCK ON FEATURE
- MULTIPLE ALERT TONES
- MESSAGE REMINDER TONE ALERT & LED ALERT
- EXTERNAL EARPHONE JACK
- SLIDE ON/OFF SWITCH WITH VIBRATE, & ALERT SELECTIONS
- STANDARD DESKTOP CHARGER
- OPERATES ON ONE AA NI-HM OR NI-CAD RECHARGEABLE BATTERY OR ONE AA ALKALINE BATTERY
- 2 STATUS LED ALERT LIGHTS
- MANUAL RESET
- AUTO RESET REVERT WITH SQUELCH
- OPTIONAL PUSH TO LISTEN FEATURE
- PROGRAMMABLE DISABLE POWER OFF & VIBRATE FEATURES

### GENERAL SPECIFICATIONS:

FREQUENCY RANGE	143 – 174 MHz	406 – 430, 450 – 512MHz
MAX. FREQ. SEPERATION	8MHz	8 MHz
ALERT SENSITIVITY	5uv/m	5uv/m
SELECTIVITY	60dB	60dB
SPURIOUS IMAGE REJECTION	55dB	55dB
AUDIO OUTPUT (12" DISTANCE)	90/88dB	90/88dB
FREQUENCY STABILITY	10ppm	10ppm
PROGRAMMABLE ADDRESSES	6	6
VOICE STORAGE TIME	2 Minutes	2 Minutes
POWER SUPPLY	1.2V NI-HM AA BATTERY	
BATTERY LIFE	APPROXIMATELY 10 DAYS	