VP220 Voice Pager

Key Specifications/Special Features:

- 1. Two Tone Decoding Format
- 2. Twelve call per channel / 8 individual and 4 group call
- 480 seconds memory (1 16 stored voice, each for 30 seconds)
 Optional function feature
- 4. Loud clear alert level
- 5. Large volume control knobs with on/off
- 6. Function Switch: different funtion switch will be configured to 4 position
- 7. Two channels (optional)
- 8. Programmable Narrow Band / Wide Band Channel Spacing
- 9. Silent & Priority Scan (Dual Frequency model)
- 10. Caller ID / Date / Time display
- 11. IP54

VP220 Rich Sophistication:

- * Loud and clear alert level: 95dBa at 12 inches distance
- * Priority alert programmable
- * 3 AAA Ni-HM rechargeable battery or 3 AAA alkaline battery
- * Desk type charger as standard
- * Fixed alert (not voice) at Maximum alert level
- * Battery low indicate, special beep tone
- * External Earphone Jack
- * Rugged housing, Strong belt clip
- * Reminder tone with LED flash
- * LCD Display: 2 lines, 24 characters, Blue Backlight
- * 6 Status LED: RED/Amber indicator Status ; 4 battery indicator LED



Specifications:

Battery Life

Model VP-220 Voice Pager Tone Coding Two-Tone Sequential

Frequency VHF 135 ~ 174 MHz, Narrow band & wide band

Channel Spacing 12.5/25KHz Paging Sensitivity 4uV per meter 12DB SIAND Sensitivity 9.4 uV per meter Adjacent channel selectivity 60dB±25KHz Spurious & Image Rejection 55dB below carrier Frequency Stability VHF ±10ppm, UHF ±3ppm Alert Tone 95dBa at 30cm(12") 93dBa at 30cm(12") Voice

Power Consumption 9mA (without power save)
Power Supply 3 x 1.2V AAA-Size Ni -MH rechargeable battery

About 14 days (7 days without battery saver) Based on

8 hours per day & 5 messages w/ 30 sec. each

Dimension 104(L)x 62(W) x 30(H) mm

Weight (with battery) Approximately 177g