

# LED- AS112/AS112R

---

## Key Specifications/Special Features:

1. Two Line Alpha LED Display
2. 10 Characters per line
3. One Line / Two Line switchable by air command
4. Message can be enter through public paging syste
5. Please refer to our Pocsag Transmitters for on-site paging system
6. Priority Message or priority capcode trigger relay output feature ( for Model: AS112R only)



---

## AS112/AS112R Rich Sophistication:

---

- \* Display memory of 163,200 bytes
- \* 4.75" characters can be read at a distance of up to 200 feet
- \* Display 10 to 40 characters per line depending on the mode
- \* Real Time Clock (option)
- \* Wireless data input; provide 3 different data format:
- \* Text mode: Accept 2,000 characters per message. Option news and sports broadcast service via public paging system
- \* Transmitter and software are optional

---

## Specifications:

---

Model	AS112 / AS112R Alpha Sign
Frequency	138~174MHz, 408~473MHz, 929~932MHz
Bit Rate	POCSAG: 512 / 1200 / 2400bps Flex: 1600 / 3200 / 6400 bps
Channel Spacing	12.5KHz / 25KHz
Code Format	POCSAG; Flex
Capcodes	POCSAG: 6 Capcodes / Flex: 16 capcodes
Array	160 x 16
Characters	10/4.75
Dimension	Case: 710 (L) x 160(H) x 70(D) mm
Weight	Approximately 3,865 g