

LED- AS122/AS122R

Key Specifications/Special Features:

1. Two Line Alpha LED Display
2. 20 Characters per line
3. One Line / Two Line switchable by air command
4. Message can be enter through public paging syste
5. Please refer to our Pocsag Transmitters for on-site paging system
6. Priority Message or priority capcode trigger relay output feature (for Model: AS122R only)



AS122/AS122R Rich Sophistication:

- * Display memory of 163,200 bytes
- * 4.75" characters can be read at a distance of up to 200 feet
- * Display 10 to 40 characters per line depending on the mode
- * Real Time Clock (option)
- * Wireless data input; provide 3 different data format:
- * Text mode: Accept 2,000 characters per message. Option news and sports broadcast service via public paging system
- * Transmitter and software are optional

Specifications:

Model	AS122 / AS122R Alpha Sign
Frequency	138~174MHz, 408~473MHz, 929~932MHz
Bit Rate	POCSAG: 512 / 1200 / 2400bps Flex: 1600 / 3200 / 6400 bps
Channel Spacing	12.5KHz / 25KHz
Code Format	POCSAG; Flex
Capcodes	POCSAG: 6 Capcodes / Flex: 16 capcodes
Array	320 x 16
Characters	10/4.75
Characters Size	16 (H) x 8 (W) mm for one line; 8 (H) x 6 (W) mm for two line
Dimension	Case: 1313 (L) x 160(H) x 70(D) mm
Weight	Approximately 6.930 g