

VP200 Pro-1 Voice Pager



Key Specifications/Special Features:

1. Two Tone Decoding Format
2. Twelve call per channel / 8 individual and 4 group call
3. 240 seconds memory (1 - 4 stored voice, each for 30 seconds) optional function feature
4. Loud clear alert level
5. Large volume control knobs with on/off
6. Function Switch: different function switch will be configured to 4 position
7. Two channels (optional)
8. Silent & Priority Scan (Dual Frequency model)
9. Programmable Narrow Band / Wide Band Channel Spacing
10. IP54

VP200 Pro-1 Rich Sophistication:

- * Loud and clear alert level: 95dBa at 12 inches distance
- * Priority alert programmable
- * 3 AAA Ni-HM rechargeable battery or 3 AAA alkaline battery
- * Desk type charger as standard
- * Fixed alert (not voice) at Maximum alert level
- * Battery low indicate, special beep tone
- * External Earphone Jack
- * Rugged housing, Strong belt clip
- * Reminder tone with LED flash
- * 6 Status LED: RED/Amber indicator Status ; 4 battery indicator LED

Specifications:

Model	VP-200 Pro-1 Voice Pager
Tone Coding	Two-Tone Sequential
Frequency	VHF 135 ~ 174 MHz, Narrow band & wide band
Channel Spacing	12.5/25KHz
Paging Sensitivity	4uV per meter
12DB SIAND Sensitivity	9.4 uV per meter
Adjacent channel selectivity	60dB±25KHz
Spurious & Image Rejection	55dB below carrier
Frequency Stability	VHF ±10ppm, UHF ±3ppm
Alert Tone	95dBa at 30cm(12")
Voice	93dBa at 30cm(12")
Power Consumption	9mA (without power save)
Power Supply	3 x 1.2V AAA-Size Ni -MH rechargeable battery
Battery Life	About 20 days (10 days without battery saver) Based on 8 hours per day & 5 messages w/ 30 sec. each
Dimension	104(L)x 62(W) x 30(H) mm
Weight (with battery)	Approximately 177g